



Optical & Performance

Receiving Device	Laser engine
Light Source	Visible Laser Diode 650 nm
Max. Resolution	4mil (0.1mm)
Scan Rate	72 scans/second
Scan Angle	46° (typical), 35°± 3° (narrow)
Printing Contrast Scale	35% Minimum
Reading Distance (DOF PCS=80%)	

Label / DOF	near	far
Code 39, 5mil	7.6 cm	12.7 cm
Code 39, 7.5mil	5 cm	20.3 cm
Code 39, 10.4mil	2.5 cm	22.8 cm
Code 39, 13mil	1.2 cm	25.4 cm

* =dependent on width of bar code

Electrical

Operation Voltage	5VDC ±0.25V
Current Consumption	700mW (140mA@5V-standby) 975mW (195mA@5V-decoding)

Mechanical

Scanner Dimension	H153*W70*L110mm
Scanner Weight	120g (without cable)

Environmental

Mechanical Shock	1M onto concrete
Operating Temperature	0°C to 40°C
Storage Temperature	-40°C to 60°C
Relative Humidity	5% to 95% non-condensing

Communication

Host Interface supported	USB & Keyboard wedge
--------------------------	----------------------

Regulation Approvals

CE, FCC, BSMI

Accessories

Stand
Cable

Functionality

Operation Mode	Trigger mode, Auto scan mode
Symbologies	All standard 1D and GS1 databar symbologies



Unitech America

Los Angeles, Houston
<http://us.ute.com> e-mail: info@us.ute.com
<http://can.ute.com> info@can.ute.com
 Mexico
<http://latin.ute.com> e-mail: info@latin.ute.com

Unitech Asia Pacific & Middle East

Taipei
<http://apac.ute.com> info@apac.ute.com / info@india.ute.com
<http://mideast.ute.com> info@mideast.ute.com

Unitech Japan

Tokyo
<http://jp.ute.com> e-mail: info@jp.ute.com

Unitech Europe

Tilburg / Netherlands
<http://eu.ute.com> e-mail: info@eu.ute.com

Unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen
<http://cn.ute.com> info@cn.ute.com
 Taipei <http://tw.ute.com> info@tw.ute.com

Headquarters

Taipei, Taiwan
<http://www.ute.com> e-mail: info@hq.ute.com